Wireless Alert TP


Wireless Alert TP is a battery-powered temperature sensor that sends a warning email if a user-set level is reached. Simply select your temperature limits and connect to any Wi-Fi network using the Wireless Alert mobile app.

- -40°C to 125°C temperature probe with 1.5m cable
- User-configurable high and low temperature limits
- Sends email alerts and scheduled status reports
- Flashing alert indicator
- Wi-Fi connected
- Simple to set up using the free mobile app
- Two years' battery life*
- No ongoing subscription fees
- Includes sticky pad for wall mounting

The Wireless Alert TP can be set up to monitor temperature limits in a variety of applications. High and low temperature limits are user-configurable between -40 and 125°C (-40 and 257°F). The device will trigger a notification email, sent to a user-selected address, if the temperature limits are breached and when the temperature returns to within those limits. In addition to this, the device can send a scheduled summary email detailing minimum, maximum and average temperature, as well as battery level, number of alerts, and total time spent in alert mode.

Specifications

| | Minimum | Typical | Maximum | Unit |
|--------------------------------------|--|---|-----------|-------------|
| Probe Measurement Range | -40 (-40) | | 125 (257) | °C (°F) |
| Device Operating Temperature | -18 (-0) | | +55 (131) | °C (°F) |
| Notification Thresholds | User configurable, within probe measurement range stated above | | | |
| Measurement Resolution | | 1 (1) | | °C (°F) |
| Measurement Accuracy | | +/-1 (-40 to +80°C) (+/-2 (-40 to +176°F)) | | °C (°F) |
| Environmental Conditions | Device: indoor use only (IP5X), Probe: waterproof (IP67) | | | |
| Probe Length | | 1.5 | | m |
| Product Dimensions (excluding probe) | 69 x 32 x 22 (2.7 x 1.3 x 0.9) | | | mm (inches) |
| Battery Type | 2 x 1.5V Alkaline LR03/UM4/AAA | | | |
| Battery Life | | 2* | | Years |
| Wi-Fi | WPA 802.11bgn (2.4GHz)** | | | |



High Alert sor Name: Fridge One event Time: 11:32 Alert Level: 5°C

Probe Reading: 8°C AC Address: 98:88:ED:30:04:0D

> The Wireless Alert TP is simple to set up, using the free Wireless Alert app, available on Google Play or the App Store.



* Battery life is dependent on: signal strength between router/access point and Wireless Alert device, presence, volume and type of Wi-Fi traffic from other devices, operating temperature and number of Alerts sent.

** For products that are compatible with Enterprise networks, see our EL-WiFi and EL-MOTE data logging ranges.

Other Wi-Fi connected products from FilesThruTheAir™

FilesThruTheAir offer a variety of Wi-Fi connected temperature and humidity monitors. Visit **www.filesthrutheair.com** to find out if we have something to fit your application.



WWW.filesthrutheair.com/wireless-alert FilesThruTheAir™ is a trademark of Corintech Ltd. Ashford Mill, Station Road, Fordingbridge, Hampshire, SP6 1DZ, UK



CE 🗵 FC



