THERMA WATERPROOF THERMOMETER

- Interchangeable thermocouple probes
- Waterproof IP66/67, robust design
- Integrated rubber seal for durability
- Large, easy to read backlit LCD

The Therma Waterproof thermometer is housed in a robust waterproof black ABS case which offers IP66/67 protection. The thermometer utilises state of the art electronic circuitry, designed for reliability and ease of use and can be submerged or washed under a running tap - ideal for industrial applications.

The thermometer measures temperature over the range of -99.9 to 299.9 °C with a 0.1 °C resolution, auto-ranging to 1 °C resolution over the range of 300 to 1372 °C.

The Therma Waterproof thermometer features a large easy to read, LCD display with max/min, hold, open circuit, low battery indication and a user selectable backlight. The unit also incorporates an auto-power off facility that automatically turns the instrument off after ten minutes, maximising battery life.

Each unit is housed in a durable, ABS case that incorporates an integrated rubber seal to ensure complete water tightness and help reduce the possibility of damage in harsh environments.

We offer an extensive range of interchangeable type K thermocouple probes, for a variety of different applications, see pages 75 to 81 for full details.



Order code	Description	
232-101	Therma Waterproof	
143-162	Penetration probe	
830-257	Protective silicone boot - black	
The Therma Waterproof is exclusive of probe		





OPTIONAL ACCESSORIES:

- Protective silicone boot. Various colours are available - see page 38 for details
- Anti-bacterial Probe Wipes helps reduce bacterial growth - see page 35

















	GUARANTEE BRITAIN	
Specification	Therma Waterproof	
Range 0.1 °C	-99.9 to 299.9 °C	
Range 1 °C	300 to 1372 °C	
Resolution	0.1 °C to 299.9 °C thereafter 1 °C	
Accuracy	±0.4 °C ±0.1 % of reading	
Battery	3 x 1.5 volt AAA	
Battery life	10000 hours	
Sensor type	K thermocouple	
Display	15 mm LCD	
Dimensions	32 x 71 x 141 mm	
Weight	220 grams	
FREE traceable certificate of calibration included		