## FOOD CHECK THERMOMETER & PROBE

- Ideal for HACCP procedures
- FREE traceable certificate of calibration
- Temperature range -49.9 to 299.9 °C
- Compact & robust design

The Food Check is designed specifically for the food and catering professional who wishes to purchase an economically priced digital thermometer. The Food Check thermometer will measure temperature quickly and accurately when monitoring cooked and chilled foods as part of HACCP and health and safety procedures.

The thermometer is housed in a user-friendly ABS case that includes Biomaster Antimicrobial Technology which reduces bacterial growth. The Food Check features a large, easy-to-read, LCD display with open circuit and low battery indication. The instrument incorporates a simple-to-use on/off push-button and is powered by three AAA batteries that give a minimum of five years of battery life. The Food Check will power off automatically after ten minutes, maximising battery life.

Each Food Check is supplied with a permanently attached food penetration probe with a 130 mm stainless steel stem and 500 mm PVC lead. This is the ideal choice for routine food inspections.



- Stainless steel wall bracket & white silicone boot (832-050)
- Anti-bacterial wipes see page 34







The Food Check is water-resistant to IP65 when used in conjunction with this boot. Protects from accidental damage. Various colours are available - see page 13.









| Order code | Description                      |
|------------|----------------------------------|
| 221-018    | Food Check - white               |
| 221-028    | Food Check - yellow              |
| 221-038    | Food Check - green               |
| 221-048    | Food Check - red                 |
| 221-058    | Food Check - blue                |
| 830-221    | Protective silicone boot - white |
| 832-050    | S/steel wall bracket & boot      |

| Specification                                      | Food Check                                 |  |
|--|--|--|
| Range  | -49.9 to 299.9 °C                          |  |
| Resolution   | 0.1 °C                                     |  |
| Accuracy   | ±0.4 °C (-49.9 to 149.9 °C) otherwise ±1 % |  |
| Battery & life                                     | 3 x 1.5 volt AAA - 10000 hours             |  |
| Sensor type  | K thermocouple                             |  |
| Display  | 12 mm LCD                                  |  |
| Dimensions   | 25 x 56 x 128 mm                           |  |
| Weight   | 160 grams                                  |  |
| FREE traceable certificate of calibration included |  |  |

